



For heating and cooling

100%

FOSSIL-FREE
ELECTRIC
MOBILE
AUTOMATIC



Mobile air-to-air heat pumps

MWK40, MW40 and MW80

From the
development phase
to the product






Mobile air-to-air heat pumps for heating and cooling

Environmentally friendly heating and cooling for all requirements



Environmentally friendly



Economical



Fossil-free



Mobile



Compact

The transformation in heat supply from fossil energy sources to regenerative concepts faces challenges, specifically regarding temporary solutions, as the resulting complexity often cannot be combined with the necessary flexibility.

With unstable price developments of fossil fuels and increasing CO₂ taxation, heat pumps offer an uncomplicated as well as sustain-

able and yet cost-effective heating solution. Depending on the version, our durable and easily transportable air-to-air heat pumps provide heating, as well as heating and cooling, completely without fossil fuels. Heating oil and gas are no longer required – an electricity connection is all that is needed.

Our **MWK40** allows year-round temperature control with just one unit

including mobile heating down to -10°C and cooling up to +40°C.

Our **MWK40** and **MW80** are designed for facing extreme temperature ranges down to -20°C but without the cooling function. Thanks to the air-to-air functionality, costly room installations are usually completely unnecessary. Any further installations of boilers or cooling units, radiators, and their pipe distributions with

Also in summer, you can keep a cool head at all times:

Our mobile heating/cooling combination **MWK40** handles outside temperatures up to +40°C and cools your objects without any problems.



MWK40/
MW40



Areas of application

- (Large) construction sites
- Warehouses and production halls
- (Large) events
- (Festival) tents
- Agriculture
- Commercial, municipal, and private requirements such as temporary heating, replacement heating in case of failure of stationary heating systems or temperature control/air conditioning.



Award

The Plus X Award is **one of the world's biggest innovation prizes for technology, sports and lifestyle**, with independent expert jurors from over 80 industries and more than 700 participating international brands.

The expert jury, consisting of editors, designers and industry experts, awards various quality seals to products that stand out for their genuine quality and innovative edge.

Our MWK40 earned the quality seal in five of a total of seven categories.





pumps, fittings and control technology become unnecessary.

Outside-installed heat pumps temper the room air directly to the desired target temperature via a circulating airflow. Mobile air-to-air heat pumps have been designed for quick installation and commissioning. The temperature control solution is ready for operation within a very short time.

No tank systems, no fuel storage, and much lower maintenance – thanks to the air-to-air operation, you also don't have to worry about water chillers compared to air-to-water heat pumps. Inlet and outlet nozzles are recessed in the housing. There are no protruding components. Safe loading is ensured by openings for forklift trucks. The high external pressure allows long hose connections.

Air-to-air heat pumps can also be used for stationary applications with a permanently installed air duct system.

With the help of a web application and a mobile internet connection, all devices can be managed, monitored and billed.

Characteristics

- Scroll-Compressor
- Refrigerant R410A
- Axial blowers with sickle blades
- Radial fan
- Via frequency inverter speed-controlled blowers for the optimum air volume
- 200 Pa external delivery pressure
- Purely electrical operation with 400 V/50 Hz/32 A
- Pressure transmitter for low and high pressure side
- Dimensions: 2.400 x 1.200 x 2.200 mm (L x W x H)
- Heat capacity 42,9 kW
- Cooling capacity 33,5 kW
- Application ambient temperature -10 °C bis +40 °C
- Maximum efficiency COP 2.88/EER 3.3
- Volume 8.000 m³/h



Info

Even under extreme conditions of up to -10°C or -20°C outside temperature, our mobile heat pumps provides enough heat for your properties, completely fossil-free – for 100 percent comfortable indoor climate.

Remote control via web browser.

Special colors available on request.

MW80



Technical Data

Power range 14 to 81 kW

			MWK40	MW40	MW80
		Artikel-No.	300686	301531	301532
Function			Heating and cooling	Heating	Heating
Application ambient temperature		°C	–10 to +40	–20 to +25	–20 to +25
Heat capacity	(A7/L35)	kW	42,9	42,4	100,4
Cooling capacity	(A30/L12)	kW	33,5	–	–
COP _h	(A-7/L35) without utilizable medium		2,24	2,30	2,34
COP _h	(A2/L35) without utilizable medium		2,88	2,76	2,77
COP _h	(A7/L35) without utilizable medium		3,31	3,07	3,06
SCOP _h	without utilizable medium		2,88	2,72	2,73
COP _h	(A-7/L35) with utilizable medium		1,95	1,96	2,04
COP _h	(A2/L35) with utilizable medium		2,50	2,42	2,46
COP _h	(A7/L35) with utilizable medium		2,88	2,69	2,71
SCOP _h	with utilizable medium		2,45	2,34	2,38
Volume		m³/h	8.000	8.000	16.000
External pressure		Pa	200	200	250
Electrical connection		V/Ph/Hz	400/3/50	400/3/50	400/3/50
Connector plug			32A CEE	32A CEE	63A CEE
Max. nominal current		A	31	31	62
Connection Ø air current		mm	525	525	525
Length		mm	2.400	2.400	3.000
Width		mm	1.200	1.200	2.300
Height		mm	2.200	2.200	2.350
Weight		kg	1.000	1.100	2.700
Sound pressure level		dB(A)	66	66	68
Refrigerant			R410A	R454C	R454C
Compressor			Scroll	reciprocating compressor	reciprocating compressor
Condensate quantity max.		liter/h	10	10	20
Nozzle condensate drain	(external)	Zoll	1 1/4	1 1/4	1 1/4

A – ambient temperature (°C) | **L** – room air temperature (°C) | **COP** – coefficient of performance (h – heating/c – cooling) | **SCOP** – annual performance

Accessories

MWK40, MW40, MW80

Hot air hose with fastening belt and carrying bag	7,6 m	Ø 305 mm	Artikel-No.	005597
--	-------	----------	-------------	--------

Options for the MWK40, MW40 and MW80

Remote query (extra charge)

Our **heat pumps** are equipped with a router by default. This provides you with a **Wi-Fi connection** and control on-site with a range of approx. 5 meters.

Optionally, remote access to operating parameters can be booked throughout Europe. In addition to remote queries of the devices, operating data and the device status can also be viewed.

On request, we can add further options to the access, such as the retrieval of historical data.



Remote maintenance (extra charge)

Upon request, we can offer **remote maintenance** of your devices.

We not only take care of the **maintenance** of your heat pumps but also provide you with regular **diagnostic reports** of the operating status.

In addition, we take care of **necessary software updates**.

Our availability on working days between 8 am and 4 pm is guaranteed.



Do you have any other requirements which are not listed here?

Please do not hesitate to contact us!

We have both the engineering know-how and the mechanical equipment to implement your individual requirements with our usual Kroll Energy quality.

Together, we can master any air-conditioning challenge and reach your desired temperatures environmentally- and budget-friendly.



Application examples



**Kroll Energy GmbH**

Eduard-Breuninger-Str. 67
71522 Backnang
Phone +49 7191 9070-200
Fax +49 7191 9070-201
vertrieb@kroll.de

Technical Service

Phone +49 7191 9070-222
Fax +49 7191 9070-201
service@kroll.de

www.kroll.de

© Kroll Energy GmbH, version 01/2024_EN-01

Mobile air-to-air heat pumps MWK40, MW40 und MW80

Units may differ from the ones shown on the pictures.

All texts, images and graphics are protected by copyright.

All rights, including reproduction, publication and processing, are reserved.

Photos, Graphics: © Kroll Energy GmbH, unsplash: antony-trivet/troy-mortier/victor/richard-t,
Adobe Stock: Serghei V/stockphoto mania/dvad/Smileus/Frank Wagner, Freepik: Ulcons.

Terms of delivery according to terms and conditions.

Technical changes reserved. All prices in euros plus statutory VAT.

Management: Klaus Stetter, Marcus Püttmer